

Notified Body No 0836

British Board of Agrément
Bucknalls Lane
Watford
Hertfordshire WD25 9BA

Telephone: 01923 665300 Facsimile: 01923 665301 e-mail: mail@bba.star.co.uk website: www.bbacerts.co.uk

Certificate of Conformity of the Factory Production Control 0836-CPR-14/F097

In compliance with the Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this Certificate applies to the construction product:

Canopy's Shelters and Walkways

Harmonised Standard	Type/model class of the construction product	Declaration method
EN 1090-1 : 2009 + A1 : 2011	Structural steel components: Up to and including Execution Level 2 according to EN 1090-2: Buildings only.	Methods 2, 3a and 3b according to table A1 : EN 1090-1

produced by: Broxap Limited

Rowhurst Close, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD

and produced in the manufacturing plants:

Broxap Limited

Rowhurst Close, Chesterton, Newcastle-under-Lyme, Staffordshire, ST5 6BD

Keep it Kool

Structure House, Grove Close, Eastcote, Northants NN128NG

This Certificate attests that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of the standard:

EN 1090-1 : 2009 + A1 : 2011

under system 2+ for the performances set out in this certificate are applied and that the factory production control fulfils all the prescribed requirements for these performances.

This Certificate was first issued on 11 June 2014 and remains valid for as long as the test methods and/or factory production control requirements included in the harmonised standard, used to assess the performance of the declared characteristics, do not change, and the construction product, and the manufacturing conditions in the plant are not modified significantly, unless suspended or withdrawn by the factory production certification body.

Signed on behalf of the British Board of Agrément:

Date of issue: 11 June 2014 Peter Maddern

Expiry Date: 11 June 2017 Head of Contractor & System Certification



Notified Body No 0836

British Board of Agrément
Bucknalls Lane
Watford
Hertfordshire WD25 9BA

Telephone: 01923 665300 Facsimile: 01923 665301 e-mail: mail@bba.star.co.uk website: www.bbacerts.co.uk

Annex to:

Certificate of Conformity of the Factory Production Control 0836-CPR-14/F097

Address: Broxap, Chesterton, Staffordshire, ST5 6BD

Keep it Kool, Eastcote, Northgants, NN12 8NG

Applicable standard: EN 1090-2 : 2008 + A1 : 2011

Design process: Yes

Execution class: Up to and including EXC2 in accordance with

EN 1090-2 : 2008 + A1 : 2011

Declaration methods: Methods 2, 3a and 3b table A.1 of EN 1090-1

Parent metals: Carbon steel grades up to S355: Hot and Cold Rolled

Steel according to EN 1090-2 and Stainless Steel

304L/316L

Welding process: 131: Metal inert gas welding; MIG-welding

141: Tungsten inert gas welding; TIG-welding

Weelh

Responsible welding coordinator: Broxap: Mr Chris Zschiesche

Keep it Kool: Mr Michael Jarrold

Signed on behalf of the British Board of Agrément:

Date of issue: 11 June 2014 Peter Maddern

Expiry Date: 11 June 2017 Head of Contractor & System Certification



BROXAP hereby declares that its

Bespoke structural steel fabrications

conform to the provisions of Annex ZA, BS EN ISO 1090-1:2009+A1:2011 ${\bf System\,2+}$

Initial inspection and continuous surveillance, assessment and approval of the Factory production Controls (FPC) is conducted by:

Notified Body: British Board of Agrement (BBA)

Bucknalls Lane Garston Watford WD25 9BA

Notified Body Number: 0836

FPC Certificate Number: 0836-CPR-14/F097

Structural Characteristics

Load Bearing: Refer to project file / structural calculations

Design: According to EN 1993-1 (EC3)

Manufacturing: According to component specification and

EN 1090-2: Execution Class 2 (EXC2)

Resistance to Fire: NPD

Fatigue Strength: NPD

Manufacturing Characteristics

Tolerances on Dimensions: According to EN 1090-2

Weldability: According to EN 10025-2 Table 6

Fracture Toughness: Minimum 27J at 0°C

Deformation at serviceability limit state: NPD

Manufactured by:



Broxap Limited

Rowhurst Industrial Estate
Chesterton

Newcastle-under-Lyme Staffordshire, ST5 6BD

Tel: (01782) 564411 Fax: (01782) 564357 Email: <u>sales@broxap.com</u> Web: <u>www.broxap.com</u> Reaction to Fire: Classified: Class A1

Release of Cadmium: NPD

Release of Radioactivity: NPD

Durability: Galvanized: according to EN ISO 1461

Signed for, and on behalf of the manufacturer, by:

Donath



BROXAP hereby declares that its

Bespoke structural steel fabrications

conform to the provisions of Annex ZA, BS EN ISO 1090-1:2009+A1:2011 ${\bf System\,2+}$

Initial inspection and continuous surveillance, assessment and approval of the Factory production Controls (FPC) is conducted by:

Notified Body: British Board of Agrement (BBA)

Bucknalls Lane Garston Watford WD25 9BA

Notified Body Number: 0836

FPC Certificate Number: 0836-CPR-14/F097

Structural Characteristics

Load Bearing: Refer to project file / structural calculations

Design: According to EN 1993-1 (EC3)

Manufacturing: According to component specification and

EN 1090-2: Execution Class 2 (EXC2)

Resistance to Fire: NPD

Fatigue Strength: NPD

Manufacturing Characteristics

Tolerances on Dimensions: According to EN 1090-2

Weldability: According to EN 10025-2 Table 6

Fracture Toughness: Minimum 27J at 0°C

Deformation at serviceability limit state: NPD

Manufactured by:

broxap°

Broxap Limited

Rowhurst Industrial Estate Chesterton

Newcastle-under-Lyme Staffordshire, ST5 6BD

Tel: (01782) 564411 Fax: (01782) 564357 Email: <u>sales@broxap.com</u> Web: <u>www.broxap.com</u> Reaction to Fire: Classified: Class A1

Release of Cadmium: NPD

Release of Radioactivity: NPD

Durability: Galvanized: according to EN ISO 1461

Powder coated: according to component

specification

Signed for, and on behalf of the manufacturer, by:

13 toutes



Keep It Kool at Broxap hereby declares that its

Steel Tensile Structures

conform to the provisions of Annex ZA, BS EN ISO 1090-1:2009+A1:2011
System 2+

Initial inspection and continuous surveillance, assessment and approval of the Factory production Controls (FPC) is conducted by:

Notified Body: British Board of Agrement (BBA)

Bucknalls Lane Garston Watford WD25 9BA

Notified Body Number: 0836

FPC Certificate Number: 0836-CPR-14/F097

Structural Characteristics

Load Bearing: Refer to project file / structural calculations

Design: According to EN 1993-1 (EC3)

Manufacturing: According to component specification and

EN 1090-2: Execution Class 2 (EXC2)

Resistance to Fire: NPD

Fatigue Strength: NPD

Manufacturing Characteristics

Tolerances on Dimensions: According to EN 1090-2

Weldability: According to EN 10025-2 Table 6

Fracture Toughness: Minimum 27J at 0°C

Deformation at serviceability limit state: NPD

Reaction to Fire: Classified: Class A1

Release of Cadmium: NPD

Release of Radioactivity: NPD

Durability: Galvanized: according to EN ISO 1461

Signed for, and on behalf of the manufacturer, by:

Tel: (01327) 830906

Northants., NN128NG

Manufactured by:

Keep It Kool

Gayton Road Eastcote

Structure House Grove Close

Email: info@keepitkool.co.uk
Web: www.keepitkool.co.uk

KeepItKool at broxap



Keep It Kool at Broxap hereby declares that its

Steel Tensile Structures

conform to the provisions of Annex ZA, BS EN ISO 1090-1:2009+A1:2011
System 2+

Initial inspection and continuous surveillance, assessment and approval of the Factory production Controls (FPC) is conducted by:

Notified Body: British Board of Agrement (BBA)

Bucknalls Lane Garston Watford WD25 9BA

Notified Body Number: 0836

FPC Certificate Number: 0836-CPR-14/F097

Structural Characteristics

Load Bearing: Refer to project file / structural calculations

Design: According to EN 1993-1 (EC3)

Manufacturing: According to component specification and

EN 1090-2: Execution Class 2 (EXC2)

Resistance to Fire: NPD

Fatigue Strength: NPD

Manufacturing Characteristics

Tolerances on Dimensions: According to EN 1090-2

Weldability: According to EN 10025-2 Table 6

Fracture Toughness: Minimum 27J at 0°C

Deformation at serviceability limit state: NPD

Manufactured by: Reaction to Fire: Classified: Class A1

Release of Cadmium: NPD

Release of Radioactivity: NPD

Durability: Galvanized: according to EN ISO 1461

Powder coated: according to component

specification

Tel: (01327) 830906 Signed for, and on behalf of the manufacturer, by:

Email: info@keepitkool.co.uk

Web: www.keepitkool.co.uk

KeepItKool at broxap

Keep It Kool

Gayton Road

Eastcote

Structure House Grove Close

Northants., NN128NG